

**SECTION 1 - PRODUCT IDENTIFICATION**

**Product identifier/Trade name:** CA-401  
**Product code/Internal Identification:** KG40120  
**Product use/Description:** Quick bonding adhesive. Small container.  
**Product chemical name:** N/Ap  
**Chemical family:** N/Ap  
**MSDS preparation/review date:** December 23, 2012  
**Supplier identifier:** Asalco Inc.  
44, ch. Des Ursulines, Stanstead, Québec (Canada), J0B 3E0  
Telephone 819-876-2211 Fax 819-876-5373 Internet [www.asalco.com](http://www.asalco.com)  
**Emergency phone number:** (613) 996-6666 (CANUTEC)  
**Manufacturer identifier:** ND Industries, Inc. 1893 Barrett Road Troy, Michigan  
**Emergency phone number:** Same as supplier  
**WHMIS Classification:** B3 – Combustible liquid  
D2B – Toxic material with other toxic effects

**SECTION 2 - CHEMICAL COMPOSITION / HAZARDOUS INGREDIENTS**

Hazardous Ingredients	CAS #	% (weight)	LD <sub>50</sub> (route, specie)	LC <sub>50</sub> (specie)
Ethyl cyanoacrylate	7085-85-0	60-100	N/Av	N/Av

**SECTION 3 - HAZARDS IDENTIFICATION****Emergency Overview**

COMBUSTIBLE LIQUID. May cause a fire at temperatures above the flash point. BONDS SKIN AND EYELID INSTANTLY. May cause slight irritations to the digestive and respiratory tract, eyes and skin.

**POTENTIAL HEALTH EFFECTS** (for more details, refer to Section 11)

**Primary entry route(s):** Skin, eye, ingestion and inhalation.

**Effects of short-term (acute) and long-term (chronic) exposure:**

**Inhalation:** May cause slight irritations to the respiratory tract.

**Skin:** BONDS SKIN INSTANTLY. May cause slight irritations to skin.

**Eye:** BONDS EYELID INSTANTLY. May cause slight eye irritations.

**Ingestion:** May cause slight irritations to the digestive tract.

**SECTION 4 - FIRST AID MEASURES****Inhalation:**

Remove source of contamination or have victim move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Obtain medical attention immediately.

**Skin contact:**

Flush contaminated area with lukewarm, gently running water for at least 5 minutes or until the chemical is removed. Under running water, remove contaminated clothing. If irritation persists, obtain medical advice. Completely decontaminate clothing before reuse or discard. **Skin bonding: soak skin in water and call a Poison Control Centre. Do not force apart.**

**Eye contact:**

Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes, or until the chemical is removed, while holding the eyelid(s) open. Obtain medical attention immediately. **Eyelid bonding: see a doctor. Do not force apart.**

**Ingestion:**

NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink two glasses of water. Obtain medical attention immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

**Fire hazards/conditions of flammability:** COMBUSTIBLE LIQUID. May cause a fire at temperatures above the flash point.

**Flash point (Method):** > 65°C Tag Closed cup

**Lower flammable limit (% by volume):** N/Av

**Upper flammable limit (% by volume):** N/Av

**Sensitivity to mechanical impact:** N/Av

**Sensitivity to static discharge:** N/Av

**Auto-ignition temperature:** N/Av

**Suitable extinguishing media:** Carbon dioxide, dry chemical powder and appropriate foam.

**Special fire-fighting procedures/equipment:**

During a fire, irritating/toxic smoke and fumes may be generated. Vapours can accumulate in confined spaces, resulting in a toxicity and flammability hazard. A self-contained breathing apparatus is required for fire-fighting personnel to protect themselves from toxic products produced during the combustion. Closed containers may explode with the pressure building from the heat. Use water to cool fire exposed containers and prevent this situation.

**Hazardous combustion products:**

Carbon monoxide, carbon dioxide and other irritant gases, which may include toxic constituents.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

**Personal precautions:**

Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. Remove all ignition sources. Remove or isolate flammable and combustible materials. Wear adequate personal protective equipment (See Section 8). Ventilate area.

**Spill response/Cleanup:**

Stop the flow if it can be done safely. Keep materials which can burn away from spilled material. Prevent material from entering waterways, sewers or confined spaces. SMALL SPILLS: Put material in suitable, covered, labelled containers. Flush area with water. LARGE SPILLS: Contain spill with earth, sand, or absorbent material which does not react with spilled material. Place in suitable, covered, labelled containers. Contact fire and emergency services and supplier for advice. Contaminated absorbent material may pose the same hazards as the spilled product.

**Environmental precautions:**

For large spills, notify government occupational health and safety and environmental authorities. Confine spill, preventing it from entering sewer lines or waterways. Dispose of as per local, state and federal regulations.

**SECTION 7 - HANDLING AND STORAGE**

**Safe handling procedures:**

Before handling, it is very important that engineering controls are operating and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Do not use near welding operations, flames or hot surfaces. Ensure proper ventilation after sealed area has been treated. Avoid generating vapours/dusts. Inspect containers for leaks before handling. Label containers appropriately. Keep containers closed when not in use. Assume that empty containers contain residues which are hazardous. Do not use with incompatible materials such as strong oxidizing agents.

**Storage requirements:**

Store in a dry, cool, well-ventilated area, away from heat and ignition sources. Keep storage area clear of ignition sources. Store away from incompatible materials such as strong oxidizers. Inspect all incoming containers to make sure they are properly labelled and not damaged. Store in suitable, labelled containers. Keep containers tightly closed. Empty containers may contain hazardous residues. Keep absorbents for leaks and spills readily available. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area.

## SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

**Engineering controls:**

Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits.

**Respiratory Protection:**

Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirator if the exposure limits are unknown.

**Protective Clothing/Equipment:**

Wear chemically protective gloves (impervious), and if necessary boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective chemical safety goggles or in a splash environment in combination with a face shield. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. Separate contaminated work clothes from street clothes. Launder before reuse.

**Comments:**

Avoid contact with skin and eyes. Avoid breathing vapours/dusts. Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

**Physical state, colour and odour:** Clear colourless to straw liquid with sharp irritating odour.

**Odour threshold:** N/Av

**Ph :** N/Av

**Boiling point:** > 148.9°C

**Melting/freezing point:** N/Av

**Vapour pressure:** < 0.2 mm Hg

**Solubility in water:** Polymerizes with water.

**Coefficient of oil/water distribution:** N/Av

**Specific gravity or density (water = 1, at 4°C):** 1.06 @ 20°C

**Vapour density:** Heavier than air

**Evaporation rate:** N/Av

**% volatile by volume:** N/Av

## SECTION 10 - REACTIVITY AND STABILITY DATA

**Stability and reactivity:** Stable at room temperature, in normal handling and storage conditions.

**Polymerisation:** Hazardous polymerisation will not occur.

**Conditions to avoid:**

Avoid STRONG OXIDIZING AGENTS, some metals, strong acids and strong bases. Keep away from ignition sources.

**Materials to avoid:** Avoid STRONG OXIDIZING AGENTS, some metals, strong acids and strong bases.

**Hazardous decomposition products:** None.

## SECTION 11 - TOXICOLOGICAL INFORMATION

**Exposure limits:** N/Av for the product.

Ingredient	OSHA PEL		ACGIH TLV		Other exposure limits
	TWA	STEL	TWA	STEL	
Ethyl cyanoacrylate	N/Av	N/Av	0.2 ppm	N/Av	N/Av

**For more details, refer to Section 3.**

**Carcinogenicity:** No ingredient is listed by IARC, ACGIH, NTP or OSHA as a carcinogen.

**Teratogenicity, mutagenicity, other reproductive effects:** N/Av

**Skin sensitization:** Possible.

**Respiratory tract sensitization:** Possible.

**Synergistic materials:** N/Av

## SECTION 12 - ECOLOGICAL INFORMATION

**Environmental effects:** N/Av

**Important environmental characteristics:** N/Av

**Aquatic toxicity:** N/Av

*N/Av: not applicable*

*N/Av: not available*

**SECTION 13 - WASTE DISPOSAL****Handling and storage conditions for disposal:**

Store material for disposal as indicated in Handling and Storage (Section 7).

**Methods of disposal:**

Review federal, provincial and local government requirements prior to disposal. Disposal by controlled incineration or secure landfill may be acceptable.

**SECTION 14 - TRANSPORTATION INFORMATION****Transportation of Dangerous Goods (TDG) :**

TDG Classification: This product is not regulated for transportation by ground within Canada.

Special case: N/Av

**SECTION 15 - REGULATORY INFORMATION****In Canada****WHMIS information:**

Product is regulated according to the Controlled Product Regulation (CPR) in Canada.

*This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and this MSDS contains all the information required by the CPR.*

**Hazardous Materials Identification System (HMIS):**

HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 1 PERSONAL PROTECTION: Section 8.

HAZARD: 0 Minimal 1 Slight 2 Moderate 3 Serious 4 Severe

**National Fire Protection Association (NFPA):**

HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 1 PERSONAL PROTECTION: Section 8.

HAZARD: 0 Minimal 1 Slight 2 Moderate 3 Serious 4 Severe

**SECTION 16 - OTHER INFORMATION**

**Prepared by:** NSS ENTREPRISE INC. for Asalco Inc.

**Telephone number:** Telephone 819-876-2211 Fax 819-876-5373 Internet www.asalco.com

**References:**

1. Material Safety Data Sheets from manufacturer/supplier.
2. CSST, Répertoire Toxicologique, Les produits, 2012.
3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2012.

**Abbreviations:**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstract Service
CFR	Code of Federal Regulations (Transportation in U.S.A.)
DOT	Department of Transport (U.S.A.)
DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
LC	Lethal concentration
LD	Lethal Dosage
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
USEPA	United States Environmental Protection Agency
WHMIS	Workplace Hazardous Materials Information System

End of the MSDS