

SECTION 1 - PRODUCT IDENTIFICATION

Product identifier/Trade name: STAIN LIFT SPRAY
Product code/Internal Identification: 11454
Product use/Description: Protector. 454 g aerosol container.
Product chemical name: N/Ap
Chemical family: N/Ap
MSDS preparation/review date: December 23, 2012
Supplier identifier: Asalco Inc.
 44, ch. Des Ursulines, Stanstead, Québec (Canada), J0B 3E0
 Telephone 819-876-2211 Fax 819-876-5373 Internet www.asalco.com
Emergency phone number: (613) 996-6666 (CANUTEC)
Manufacturer identifier: Same as supplier
Emergency phone number: Same as supplier
WHMIS Classification: A – Compressed gas
 B5 – Flammable aerosol
 D1B – Toxic material with immediate and serious toxic effects
 D2A and D2B – Toxic material with other toxic effects

SECTION 2 - CHEMICAL COMPOSITION / HAZARDOUS INGREDIENTS

Hazardous Ingredients	CAS #	% (weight)	LD ₅₀ (route, specie)	LC ₅₀ (specie)
Hexane	110-54-3	15-40	25 g/kg (oral, rat)	48000 ppm 4 hours (rat)
Perchloroethylene (Tetrachloroethylene)	127-18-4	10-30	2629 mg/kg (oral, rat)	3786 ppm 4 hours (rat)
Silica, amorphous	7631-86-9	1-5	N/Av	N/Av
Isobutane	75-28-5	15-40	N/Av	142500 ppm 4 hours (rat)
Propane	74-98-6	5-10	N/Av	N/Av

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview

EXTREMELY FLAMMABLE AEROSOL. Vapours may catch fire. Content under pressure. Poison. Harmful or fatal if inhaled. May cause headache, nausea, dizziness, other central nervous system effects, and eventually respiratory failure and death. May be harmful if swallowed. Causes eye, skin and respiratory irritation. Contains material which may cause peripheral nervous system damage. Possible cancer hazard – Contains material which may cause cancer.

POTENTIAL HEALTH EFFECTS (for more details, refer to Section 11)

Primary entry route(s): Skin, eye, ingestion and inhalation.

Effects of short-term (acute) and long-term (chronic) exposure:

Inhalation:

May cause severe irritation to the nose, throat and respiratory tract, and central nervous system depression. Symptoms may include headache, nausea, vomiting, loss of coordination, and eventually respiratory failure and death. In extremely high concentrations, product may act as an asphyxiant and cause increased breathing and pulse rates, fatigue, nausea, vomiting and unconsciousness.

Skin:

May cause severe skin irritations.

Eye:

May cause slight to moderate eye irritations.

Ingestion:

Prolonged or excessive ingestion may cause aspiration of liquid into the lungs and cause chemical pneumonitis or even death. May also cause gastrointestinal irritation, nausea and diarrhea.

SECTION 4 - FIRST AID MEASURES**Inhalation:**

Remove source of contamination or have victim move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Obtain medical attention immediately.

Skin contact:

Flush contaminated area with lukewarm, gently running water for at least 20 minutes. If irritation persists, obtain medical advice.

Eye contact:

Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 20 minutes. Obtain medical attention immediately.

Ingestion:

NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Repeat administration of water. Obtain medical attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability: EXTREMELY FLAMMABLE AEROSOL according to flame projection (> 45 cm) and no flashback available. Does burn under normal handling conditions.

Flash point (Method): -23°C (Tag closed cup) for Hexane

Lower flammable limit (% by volume): 1.0

Upper flammable limit (% by volume): 9.5

Sensitivity to mechanical impact: Aerosols may explode or become projectiles after a mechanical impact.

Sensitivity to static discharge: N/Av

Auto-ignition temperature: 225°C

Suitable extinguishing media: Carbon dioxide, dry chemical powder and appropriate foam.

Special fire-fighting procedures/equipment:

During a fire, irritating/toxic smoke and fumes may be generated. Vapours can accumulate in confined spaces, resulting in a toxicity and flammability hazard. A self-contained breathing apparatus is required for fire-fighting personnel to protect themselves from toxic products produced during the combustion. Closed containers may explode with the pressure building from the heat. Use water to cool fire exposed containers and prevent this situation.

Hazardous combustion products:

Carbon monoxide, carbon dioxide and other irritant gases, which may include toxic constituents.

SECTION 6 - ACCIDENTAL RELEASE MEASURES**Personal precautions:**

Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. Remove all ignition sources. Remove or isolate flammable and combustible materials. Wear adequate personal protective equipment (See Section 8). Ventilate area.

Spill response/Cleanup:

Stop the flow if it can be done safely. Keep materials which can burn away from spilled material. Prevent material from entering waterways, sewers or confined spaces. Put material in suitable, covered, labelled containers.

Environmental precautions:

Confine spill, preventing it from entering sewer lines or waterways. Dispose of as per local, state and federal regulations.

SECTION 7 - HANDLING AND STORAGE**Safe handling procedures:**

Before handling, it is very important that engineering controls are operating and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Do not use near welding operations, flames or hot surfaces. Ensure proper ventilation after sealed area has been treated. Inspect containers for leaks before handling. Label containers appropriately. Keep containers closed when not in use. Empty containers are always dangerous. Assume that empty containers contain residues which are hazardous. Do not use with incompatible materials.

Storage requirements:

Store in a cool, well-ventilated area, away from heat and ignition sources. Keep storage area clear of ignition sources. Store away from incompatible materials. Inspect all incoming containers to make sure they are properly labelled and not damaged. Store in suitable, labelled containers. Keep containers tightly closed. Empty containers are always dangerous. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION**Engineering controls:**

None required under normal handling conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits.

Respiratory Protection:

None required under normal handling conditions. Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirator if the exposure limits are unknown.

Protective Clothing/Equipment:

If necessary, wear chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact. Wear protective chemical safety glasses to prevent prolonged or repeated eye contact. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Comments:

Avoid contact with skin and eyes. Avoid breathing this product. Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state, colour and odour:	Aerosol (off-white) with slight petroleum odour.		
Odour threshold:	N/Av		
pH:	N/Av		
Melting/freezing point:	N/Av		
Coefficient of oil/water distribution:	N/Av		
Specific gravity or density (water = 1):	~0.976-0.988	Boiling point:	N/Av
Evaporation rate (n-Butyl acetate = 1):	< 1	Vapour pressure (@ 20°C):	28-40 psig @ 20°C
		Solubility in water:	Negligible
		Vapour density (Air = 1):	> 1 heavier than air
		% volatile by volume:	N/Av

SECTION 10 - REACTIVITY AND STABILITY DATA

Stability and reactivity:	Stable under the recommended storage and handling conditions prescribed.
Polymerization:	Hazardous polymerization will not occur.
Conditions to avoid:	Avoid STRONG OXIDIZING AGENTS. Keep away from ignition sources. Do not expose containers to mechanical impacts and temperatures exceeding 50 °C (122°F).
Materials to avoid:	Avoid STRONG OXIDIZING AGENTS.
Hazardous decomposition products:	Hydrogen chloride gas, Chlorine, Phosgene. Refer to 'Hazardous combustion products', Section 5.

SECTION 11 - TOXICOLOGICAL INFORMATION

Exposure limits: N/Av for the product.

Ingredient	OSHA PEL		ACGIH TLV		Other exposure limits
	TWA	STEL	TWA	STEL	
Hexane	50 ppm	N/Av	50 ppm	N/Av	N/Av
Perchloroethylene (Tetrachloroethylene)	25 ppm	N/Av	25 ppm	100 ppm	N/Av
Silica, amorphous	N/Av	N/Av	N/Av	N/Av	N/Av
Isobutane	N/Av	N/Av	N/Av	N/Av	1000 ppm
Propane	N/Av	N/Av	N/Av	N/Av	1000 ppm

For more details, refer to Section 3.

Carcinogenicity:

Perchloroethylene (Tetrachloroethylene) is listed by IARC, ACGIH, NTP or OSHA as a possible carcinogen.

Teratogenicity, mutagenicity, other reproductive effects: N/Av

Skin sensitization: N/Av

Respiratory tract sensitization: N/Av

Synergistic materials: N/Av

SECTION 12 - ECOLOGICAL INFORMATION

Environmental effects: N/Av

Important environmental characteristics: N/Av

Aquatic toxicity: N/Av

SECTION 13 - WASTE DISPOSAL

Handling and storage conditions for disposal:

Store material for disposal as indicated in Handling and Storage (Section 7).

Methods of disposal:

Review federal, provincial and local government requirements prior to disposal.

SECTION 14 - TRANSPORTATION INFORMATION

Transportation of Dangerous Goods (TDG) :

TDG Classification: AEROSOLS; Class 2.1; UN1950

Special case: Product can also be shipped as a LIMITED QUANTITY/CONSUMER COMMODITY according to TDG Section 1.17.

SECTION 15 - REGULATORY INFORMATION

WHMIS information:

Product is regulated according to the Controlled Product Regulation (CPR) in Canada.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and this MSDS contains all the information required by the CPR.

Hazardous Materials Identification System (HMIS):

HEALTH: 2 FLAMMABILITY: 4 REACTIVITY: 1 PERSONAL PROTECTION: Section 8.

HAZARD: 0 Minimal 1 Slight 2 Moderate 3 Serious 4 Severe

National Fire Protection Association (NFPA):

HEALTH: 2 FLAMMABILITY: 4 REACTIVITY: 1 PERSONAL PROTECTION: Section 8.

HAZARD: 0 Minimal 1 Slight 2 Moderate 3 Serious 4 Severe

United States OSHA information:

This product is regulated according to OSHA. This MSDS contains all the information required by OSHA.

United States TSCA information: The ingredients in this product are listed on the TSCA.

New Jersey Labeling Requirements: Ingredients to be disclosed on product labelling : Refer to Section 2.

California Proposition 65: This product contains a chemical that is known to the State of California to cause cancer or other reproductive harm.

SECTION 16 - OTHER INFORMATION

Prepared by: NSS ENTREPRISE INC. for Asalco Inc.
Telephone number: Telephone 819-876-2211 Fax 819-876-5373 Internet www.asalco.com

References:

1. Material Safety Data Sheets from manufacturer/supplier.
2. CSST, Répertoire Toxicologique, Les produits, 2012.
3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2012.

Abbreviations:

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstract Service
CFR	Code of Federal Regulations (Transportation in U.S.A.)
DOT	Department of Transport (U.S.A.)
DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
LC	Lethal concentration
LD	Lethal Dosage
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
USEPA	United States Environmental Protection Agency
WHMIS	Workplace Hazardous Materials Information System

End of the MSDS